



INTERNATIONAL ROAD DYNAMICS INC. www.irdinc.com

.

MANAGEMENT

We make

- SAFETY
- PRESERVATION

International Road Dynamics
Inc. develops and maintains
traffic management products
and systems technology that
make highways talk. What are
they saying? They are
providing information that
roadway administrators need
to manage traffic, preserve
infrastructure and provide
safety warnings to drivers.

IRD's multi-discipline, innovative and customerfocused team is expert in advanced technologies, advanced traffic solutions and custom-designed systems.



DAW 300 PCMobile Weighing System

The DAW 300 is a portable Weigh-In-Motion System. The weighing system can be installed on any level area within minutes. The weighing capacity is 20 tons per axle and can weigh vehicles at speeds up to 40 mph with permanently installed bending plates. The microprocessor controlled electronics are built into a rugged, portable metal enclosure. The loads which have been measured are displayed on the PC and can printed on the tape printer. Limits for axle and total weights are programmable. Alarm tone will sound when pre-programmed weight limits are exceeded.



DAW 300 PC

FEATURES

- Portable
- High speed thermal dot matrix printer
- Printouts: gross weight, axle loads, group
- loads, limits and overloads
- Portable or permanent weighing plates
- Display all violations
- Automatic operation available

DAW 300 PC

Specifications

DAW Portable Weighing Plates

The dynamic weighing plate consist of a high-strength thin steel plate. Wire strain gauges are used for measuring the load. The entire weighpad is covered with hot vulcanized neoprene rubber. The weighing plate is equipped with handles and is connected to the electronics unit by a cable. The handle opposite to the cable connector is equipped with rollers for easy movement. For best accuracy the weigh plates are installed in shallow pits so that their surfaces are flush with the roadway. For temporary installations the weigh plates can be placed on level ground with approach and departure ramps.



Portable Installation



Mobile Housing



Portable Bending Plate

TECHNICAL DATA DAW 300

Bending Plate

Size: 116.8 cm x 50.8 cm x 2.3 cm

46 in x 20 in x .9 in

Weight: 67.9 kg

150 lbs

Temp: -40° C to 80° C

-40° F to 176° F

Weight Per Axle: 498 kg to 19, 910 kg

1,100 to 44,000 lbs

Speed Range: 4.8 to 64.5 kph

3 to 40 mph

Accuracy: \pm +/- 3% (up to 8 mph)

+/- 4% (8 to 15 mph)

Electronics

Size: 49.5 cm x 34.5 cm x 19.1 cm

19.5 in x 13.6 in x 7.5 in

Weight: 6 kg

13.2 lbs

Temp: -35° C to 70° C

-30° F to 158° F

Laptop: 0° C to 50° C

32° F to 122° F





IRD-PAT Traffic

1002 S. Main Street Chambersburg, PA USA 17201 Tel: 1-877-444-4IRD (4473) Fax: (306) 242-5599

IRD Corporate Office

702-43rd Street East Saskatoon, Saskatchewan Canada S7K 3T9 Tel: (306) 653-6600 Fax: (306) 242-5599

Publicly Traded on the TSX (Symbol IRD)

Find out more about IRD on our website: www.irdinc.com or email: info@irdinc.com

IRD products and components are protected by one or more worldwide patents and/or trademarks. IRD reserves the right to change, modify, or improve its products at any time without notice.